

# CARBON DIOXIDE

**CARBON DIOXIDE** is discharged as a white cloud of “snow” which smothers a fire by eliminating oxygen. It is effective for Class B flammable liquids and is electrically non-conductive. Carbon Dioxide is a clean, non-contaminating, odorless gas.

## RUGGED

- 5-Year Manufacturer’s Warranty
- All-Metal Valve Construction
- Rust-Free Aluminum Cylinders
- Durable High-Gloss Polyester Powder Paint
- Temperature Range -22°F to 120°F

## USER FRIENDLY


- Meets Many Hospital Medical Equipment Requirements
- Large Loop Stainless Steel Pull Pin
- Model 322NM is Independently Tested and Approved for use in MRI Facilities to 11.7 Tesla
- Model 322NM has a Sanitary White Paint Finish (easy to clean)
- QR Coded and Bilingual Labels

## CLEAN

- Leaves No Residue

## OPTION

- USCG Approved with Bracket Listed on UL Label



### Models

332 331  
322 330



Non-Magnetic model available (Model 322NM - Tested to 11.7 Tesla).

AGENT TYPE	CARBON DIOXIDE				
VALVE TYPE					
DESIGN	TUBE & HORN		HOSE & HORN		
MODEL NUMBER	322	322NM	330	331	332
UL & ULC RATING	5B:C	5B:C	10B:C	10B:C	10B:C
CAPACITY (LBS.)	5	5	10	15	20
SHIPPING WT. (LBS.)	13.1	13.1	28.25	37.75	50.75
HEIGHT (IN.)	17.75	17.75	24	30	30
WIDTH (IN.)	8.25	8.25	12	12	13
DEPTH (IN.)	5.25	5.25	7	7	8
RANGE (INITIAL- FT.)	3-8	3-8	3-8	3-8	3-8
DISCHARGE TIME (SEC.)	9	9	11	14.5	19.2
INCLUDED BRACKET	WALL	NM WALL	WALL	WALL	WALL

AVAILABLE IN 50/100 LB. WHEELED EXTINGUISHERS

MANUFACTURED AND TESTED TO ANSI/UL STANDARDS  
COMPLIES WITH NFPA 10 STANDARD  
ISO-9001/ ISO-14001 CERTIFIED  
UL LISTED

CONFORMS TO TEST STANDARDS:  
CAN/ULC-S503 - ANSI/UL154 &  
CAN/ULC-S508 - ANSI/UL711

